

Wall mounted unit

FTXP-L + RXP-L



Energy saving during standby mode



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Whisper quiet
- › Online controller (optional)
- › Ideal for above door installation
- › Bluevolution range: lower environmental impact

- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

FTXP-L + RXP-L



Efficiency data		FTXP + RXP	20L + 20L	25L + 25L	35L + 35L	50L + 50L	60L + 60L	71L + 71L	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3	
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.70	1.7/7.0/8.00	2.3/8.2/9.00	
Power input	Cooling	Min./Nom./Max.	kW	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	0.320/1.385/1.826	0.449/2.689/3.274	
	Heating	Min./Nom./Max.	kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	0.440/1.579/2.356	0.456/1.928/2.787	0.617/2.571/3.306
Space cooling	Energy efficiency class		A++						A
	Capacity	Pdesign	kW	2.00	2.50	3.50	5.00	6.00	7.10
	SEER			6.79	6.92	6.62	6.72	6.82	5.30
	Annual energy consumption		kWh/a	104	127	186	261	308	469
Space heating (Average climate)	Energy efficiency class		A++			A+		A	
	Capacity	Pdesign	kW	2.20	2.40	2.80	4.60	4.80	6.20
	SCOP/A			4.65	4.61	4.64	4.10		3.81
	Annual energy consumption		kWh/a	662	728	845	1,570	1,637	2,278
Nominal efficiency	EER		4.02	3.83	3.49	3.61	3.29	2.64	
	COP		4.77	4.36	4.02	3.80	3.63	3.19	
	Annual energy consumption		kWh	-			693	912	1,345
	Energy labeling Directive	Cooling/Heating		A/A			-/-		

Indoor unit		FTXP	20L	25L	35L	50L	60L	71L	
Dimensions	Unit	HeightxWidthxDepth	286x770x225			295x990x263			
Weight	Unit	kg	9.00			13.5			
Air filter	Type		Removable / washable						
Fan	Air flow	Cooling	Silent operation/Low/Medium/High	m ³ /min	4.4/5.9/7.9 / 9.8	4.4/6.1/8.1 / 10.1	4.5/6.3/8.3 / 11.5	10.5/11.9/14.4 / 16.8	10.7/12.2/14.8 / 17.3
	rate	Heating	Silent operation/Low/Medium/High	m ³ /min	5.3/6.5/8.4 / 10.3	5.3/6.7/8.6 / 10.3	5.3/7.0/9.0 / 11.5	10.7/12.2/14.8 / 17.3	11.3/12.8/15.8 / 17.9
Sound power level	Cooling		dBA	55		58	59	60	62
	Heating		dBA	55		58	61	62	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20/25/39	20/26/40	20/27/43	31/34/43	33/36/45	34/37/46
	Heating	Silent operation/Low/High	dBA	21/28/39	21/28/40	21/29/40	30/33/42	32/35/44	33/36/45
Control systems	Infrared remote control		ARC480A11						
	Wired remote control		BRC944B2 / BRC073A1			BRC073A1			
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						

Outdoor unit		RXP	20L	25L	35L	50L	60L	71L	
Dimensions	Unit	HeightxWidthxDepth	550x658x275			734x870x373			
Weight	Unit	kg	28			46.0	50.0		
Sound power level	Cooling		dBA	60		62	61	63	66
	Heating		dBA	61		62	61	63	65
Sound pressure level	Cooling	Nom./High	dBA	-/46		-/48	47/-	49/-	52/-
	Heating	Nom./High	dBA	-/47		-/48	49/-		52/-
Operation range	Cooling	Ambient	Min.~Max.	°CDB			-10~46		
	Heating	Ambient	Min.~Max.	°CWB			-15~18		
Refrigerant	Type		R-32						
	GWP		675.0						
	Charge		kg/TCO2Eq	0.70/0.48		0.90/0.61	1.15/0.78		
Piping connections	Liquid	OD	mm	6,35			6,4		
	Gas	OD	mm	9,5			12,7		
	Piping length	OU - IU	Max.	m			15		
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)					
	Level difference	IU - OU	Max.	m			12		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)	A	-			16			