



Console



Features: ● Standard ○ Optional

Light Commercial

AIR CONDITIONERS
CATALOGUE



► Slim body and flexible installation

Properly match with various indoor decorations and various buildings, meeting your needs for comfort. Installed on the floor.



► Smart WiFi

Even though you are not in the room, you can remotely control the air conditioner via mobile phone, tablet computer or other mobile devices.



INVERTER
GREE

Model			GEH09AA-K3DNA1D	GEH12AA-K3DNA1D	GEH18AA-K3DNA1D
Function			Cooling/Heating	Cooling/Heating	Cooling/Heating
Capacity	Cooling	Btu/h	9200	11900	11700
	Heating	Btu/h	9500	12800	18100
	Pdesignh	Btu/h	9200	11900	11700
SEER/SCOP(A)	W/W	6,50/4,00	6,40/4,0	6,50/4,1	
Energy Class			A++/A+/A+++/B	A++/A+/A+++/B	A+/A+++/A+/A
Power Supply	Ph, V, Hz		1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz
Power Input	Cooling	W	735	1100	1600
	Heating	W	745	1000	1500
Rated Current	Cooling	A	5,85	5,9	10,9
	Heating	A	6,25	7	11,1
Airflow Volume	Indoor	m ³ /h	500/430/410/370/330/280/250	600/520/480/440/400/360/280	700/650/580/520/460/410/320
Indoor Unit					
Sound Pressure Level	Indoor	dB(A)(SHHML)	40/36/34/32/30/26/23	42/40/38/36/34/31/25	47/45/42/40/37/35/31
Outline Dimension	WxHxD	mm	700×215×600	700×215×600	700×215×600
Package Dimension	WxHxD	mm	788×283×685	788×283×697	788×283×697
Net Weight/Gross Weight	Indoor	kg	15,5/18,5	15,5/18,5	15,5/18,5
Outdoor Unit					
Sound Power Level	Outdoor	dB(A)	52	52	57
Piping Connection	Gas	mm	φ9,52	φ9,52	φ12
	Liquid	mm	φ6	φ6	φ6
Outline Dimension	WxHxD	mm	776×540×320	776×540×320	955×700×396
Package Dimension	WxHxD	mm	823×358×595	823×358×595	1029×458×750
Net Weight/Gross Weight	Outdoor	kg	31/33,5	31,5/34	46/50,5
Loading Quantity	40/GP	sets	180	180	121
	40/HQ	sets	201	201	133

1. The product with "i" is under development, and the parameters are estimated, please refer to the value on nameplates.
2. Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.